

W-4600CPR



In-line Automatic Wrapper

Wrap a wide range of tray sizes quickly and simply, streamline your wrapping operation



Wrapper

W-4600CPR

W-4600CPR

In-line Automatic Wrapper



**Tray presser
for better
sealing**



**Large color
touch screen**



Gravity infeed roller



Infeed conveyor
Automatic centering infeed conveyor



Straight-through gravity outfeed roller
U-turn conveyor



W-4600CPR with optional Infeed conveyor and straight-through gravity outfeed roller



Simple film loading

Specifications

Wrapping

Package size — Width: 130 - 380mm / 5.1 - 15 inches
Height: 10 - 150mm / 0.4 - 5.9 inches
Depth: 80 - 260mm / 3.1 - 10.2 inches

The maximum combination of the above dimensions is not available and the available package size depends on the film width. Please contact your distributor for specific package sizes.

Film size — Width: 300/350/400/450/500 mm,
Length: 1,500m (max.)

Number of film roll — One roll
Wrapping speed — 30 packages/min. (max.)
Wrapping capacity — 5kg, 11 lb (max.)

Console

Display panel — 10.4 inches TFT color
Keypad — Pictogram or English
Programmable items — Tray data, Wrapping conditions, PLU data

General

Externals — Resin and stainless steel construction
Power source and power consumption — 208 / 240V; 3Ø; 50 / 60Hz; 1.0kVA
220 - 240V; 1Ø; 50 / 60Hz; 6A; 0.8kW
Net weight — 274kg / 604.06 lb
Airborne noise emissions — Equivalent continuous A-weighted sound pressure level : under 70dB
Operating humidity — 90%RH (max.)
Dimensions — 1060(W) × 836(D) × 1380(H)mm
41.7(W) × 32.9(D) × 54.3(H)inches



* Specifications are subject to change without notice.

TERAOKA SEIKO CO.,LTD.

5-13-12 Kugahara, Ohta-ku,
Tokyo 146-8580 Japan
TEL:+81-3-3752-0327 FAX:+81-3-3752-5814
http://www.digisystem.com
e-mail:info@hq.digi.co.jp

DIGI I's Ltd.

